

ARMA MOISTURE-WICKING LINING

Selected and tested for its moisture-wicking properties, comfort and durability used throughout the range.

ARMA AirSafe COMPOSITE METAL FREE

Lightweight toe and midsole protection, complete with durable non-metallic hardware that won't rust and is metal detector friendly.

ARMA COMFORT INSOLES

Using a mix of EVA and Memory Foam insole materials to provide comfort in every working environment.

ESD ELECTRO-STATIC DISCHARGE

Provides a safe and controlled method of discharging static electricity buildup the optimum choice for personal grounding.

WATERPROOF MEMBRANES

High quality waterproof and breathable linings keeping your feet dry in the worst of conditions.

YKK ZIPS

The worlds best known zip brand, used for quality and longevity giving you easy entrance and exit for your footwear.

1000V PROTECTION

Specially developed with the EV electric vehicle market in mind and tested to Class 0/1000V ASTM F 2413 - 18 and BS EN 50321 : 00 giving the wearer protection against electric shock.

3M THINSULATE LINING

Insulation is warm yet lightweight, powerful yet thin, helps trap body heat while allowing moisture to escape.

SLIP RESISTANCE

Soles tested to the highest slip resistance levels.

ISO 20345 : 2011 : All ARMA footwear is tested to the latest CE and UKCA standards.



THE Range

Our ARMA footwear is our best-selling, offering a wide range of footwear to suit all working environments because one size does not fit all. Rigourously tested to meet the highest standards and continually developed through R&D and customer feedback bringing you the best footwear on the market.



- 1 200 Joule Toe Cap
- 2 Protective Mid-Sole
- 3 Comfort Insoles
- 4 Easy Lace-Hook System
- 5 Slip Resistant Soles

Develop, Refine and Improve

We develop our footwear through a number of channels from our designers and suppliers to our customer feedback, all tested to the latest CE and UKCA standards through certified bodies. We are continually refining our footwear to bring you the most improved version of our footwear range to date. Providing comfort, durability and performance second to none.



WORKWEAR FOR INDUSTRY

BONDED FLEECE HOODED SWEATSHIRT



LCSW105 Sizes M-XL

BONDED SOFTSHELL JACKET



LCJKT450 Sizes M-XL

PADDED VEST



LCVST706 Sizes M-XL

BASIC CARGO TROUSER



LCPNT205 W: 30" - 42" L: S/R/L

CARGO TROUSER



LCPNT206 W: 30" - 42" L: S/R/L

ERGONOMIC KNEE PADS



LCKP002 ONE SIZE

HEAVY DUTY WORK SOCKS



LCSC628 ONE SIZE

HEAVY DUTY WORK SOCKS



LCSC603 ONE SIZE

CANVAS BELT



LCBLT13 ONE SIZE

- + Showerproof
- + Ease of Movement
- + Inner Phone Pocket
- + Detachable Hood
- + Windproof
- + Waterproof
- + Reflective Trim
- + Multi-Tool Pocket
- + Taped Seams
- + Reversible Jacket
- + Breathable
- + Thermal Action Fabric
- + Detachable Pockets
- + Knee Pad Pocket
- + Wicking

GLOBAL SAFETY LTD
7 Jubilee Street, Melton Mowbray, Leicestershire LE13 1ND
Telephone: 01664 482482 Fax: 01664 482483
E-mail: sales@global-safety.co.uk
www.global-safety.co.uk



Global Safety

QMS 30 - Issue 17

2021

SAFETY FOOTWEAR FOR INDUSTRY

Global Safety



Safety Ratings

Our safety footwear has been manufactured in accordance with ISO 20345:2011 standards. The safety footwear has been given a rating by classifying the correct footwear for your job requirement. All footwear is safety marked with the safety symbol. It is every individual's right of choice and is carried out in order to achieve the correct rating required.

Safety Rating EN ISO 20345

- S9 - Heat resistant and electric, 200 joule toe cap, Penetration resistant midsole.
- S8P - Basic safety protection, 200 joule toe cap, Penetration resistant midsole.
- S8 - 200 joule toe cap, Closed heel region, Antistatic, Energy absorption.
- S7P - 200 joule toe cap, Closed heel region, Antistatic, Energy absorption, Penetration resistant midsole.
- S7 - 200 joule toe cap, Closed heel region, Antistatic, Energy absorption, Water absorption.
- S6 - 200 joule toe cap, Closed heel region, Antistatic, Energy absorption, Penetration resistant midsole, Water absorption and Penetration resistant, Cleated outsole.
- S4 - 200 joule toe cap, Antistatic and polymeric outsole footwear, Energy absorption, Penetration resistant midsole, Cleated outsole.
- S3 - 200 joule toe cap, Antistatic, Energy absorption, Penetration resistant midsole, Cleated outsole.
- FR - Heat resistant Outsole 300°C.
- HI - Heat resistant heel.
- HMU - Heat resistant upper.
- AM - Antistatic upper.
- ESD - Electrostatic Discharge.

Slip Resistance

- SR4 - Tested on ceramic tile wetted with dilute soap solution.
- SR3 - Tested on ceramic tile wet with glycerol.
- SR2 - Tested on both the above conditions.